

B-EV4D B-EV4T

Desktop Printers

Datasheet

- > Toshiba's compact B-EV4 range for fast, on-demand labelling and ticketing directly from your desktop.
- > Produce professional labels quickly and easily at the touch of a button with market-leading features, exceptional build, quality, and reliability.



Compact & Convenient

Developed to fit into limited work spaces in many industries and applications, the B-EV4 is ready whenever it is required. Using the latest 32 bit Toshiba processing technology, it gives rapid on-demand printing at speeds of up to 5 inches a second.

Take Control

Design and print straight from a PC using Windows® drivers and free BarTender Ultra Light software. Print tickets and labels from 80 mm up to a market-leading 995 mm.

Flexible Models

The direct thermal model (B-EV4D) is suitable for short-term ticketing and labelling using thermal papers whereas the B-EV4T also uses thermal ribbons for more hard-wearing items. Both types have a choice of print resolution, 203 dpi for everyday uses or 300 dpi for specialist barcodes and graphics.

Specifications

General

Print Method	B-EV4D GS/TS: Direct thermal B-EV4T GS/TS: Direct thermal/Thermal transfer
Printhead	Flat head
Dimensions (W x D x H)	B-EV4D GS/TS: 198 x 258 x 173 mm B-EV4T GS/TS: 198 x 258 x 173 mm
Weight	B-EV4D GS/TS: 2.3 kg B-EV4T GS/TS: 2.4 kg
User Interface	Single LED (colours: green, amber, red)
Operating Temperature/ Humidity	5°C to 40°C / 25-85% non-condensing relative humidity (RH)
Power Supply	AC 100 to 240V, 50/60 Hz universal adapter

Print

Resolution	B-EV4D GS/TS: 203/300 dpi B-EV4T GS/TS: 203/300 dpi
Max. Print Speed	B-EV4D GS/TS: 127/101.6 mm/second B-EV4T GS/TS: 127/101.6 mm/second
Max. Print Width	B-EV4D GS/TS: 50.8/105.7 mm/second B-EV4T GS/TS: 50.8/105.7 mm/second
Max. Print Length	B-EV4D GS/TS: 995/453 mm B-EV4T GS/TS: 995/453 mm
Barcodes	UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN 128, NW7, MSI, Industrial 2 of 5, Postnet, RM4SCC, KIX-Code, RSS14, Customer Barcode, GS1 Databar
2D Codes	Data Matrix, PDF 417, Maxicode, QR Code, Micro PDF 417, CP Code
Fonts	Bitmap font, Outline font, Price font

Ribbon¹⁾

Ribbon Width	B-EV4T GS/TS: 40 to 110 mm
Ribbon Core	12.7 mm
Max. Ribbon Length	B-EV4T GS/TS: 110 m
Max. Outer Core Diameter	40 mm

Media

Alignment	Centred
Backing Paper Width	25.4-112 mm
Label Thickness	0.06-0.19 mm
Linerless Media	B-EV4D: yes (optional kit required) B-EV4T: not available
Inner Media Roll Diameter	25.4 or 38.1 mm (optional: 76.2 mm)
Outer Media Roll Diameter	Max. 127 mm
Media Type	Roll, Fanfold

Software & Connectivity

Emulation	ZPL II, EPL, DPL, IPL
Printer Driver	Windows 7/8.1, Server 2012
Host Interface	RS-232C (max. 115,200 bps), Centronics (SPP), USB 2.0 (Full Speed), LAN 10/100 Base
Label Software	BarTender Ultra Light

Options

Full cutter module, Partial cutter module. Peel-off module, External 203 mm OD media stand, Keyboard unit (KB-75-QM-R), Power cable tray, B-EV4D Linerless platen, Linerless cutter

¹⁾ B-EV4 ribbons are different from those used in its predecessor, the B-SV4. Ribbons are not available for B-FV4D models (Direct thermal).



For more information please contact us:

Toshiba Tec Germany Imaging Systems GmbH
Carl-Schurz-Str. 7
41460 Neuss
Germany

Telephone / Fax
+49 2131-1245-0 / +49 2131-1245-402

Website
www.toshiba-europe.com/tec

Together Information is Toshiba's vision for how people and organisations create, record, share, manage and display ideas and data.

It is based on our belief that the most successful organisations are those that communicate information in the most efficient way.

We make that possible through an integrated portfolio of industry specific solutions, all of which reflect Toshiba's commitment to the future of the planet.

